DISPENSERS

FOR ADHESIVE TAPES

Modern manual and electronic dispensers with adjustment and programming of stripe length, and optional colour prints.



ekoKRAFT

80-172 Gdańsk, ul. Trzy Lipy 3 tel. 58 717 51 34 kom. 607 634 850 biuro@ekokraft.com.pl ekokraft.com.pl



BP 555e ELECTRONIC

Regular/ reinforced tape Width 40- 80 mm Stripe length 150- 1.450mm 14 length setting Device dimensions: 510 x 320 x 300 mm

Weight: 15.0 kg





BP 754e ELECTRONIC

Regular/ reinforced tape Width 40- 100 mm Stripe length 150- 2.500mm 2 length setting

Device dimensions: 540 x 260 x 230 mm

Weight: 16.2 kg





BP 755e ELECTRONIC

Regular/ reinforced tape Width 40- 100 mm Stripe length 150- 1.570mm 20 length setting Device dimensions: 540 x 260 x 230 mm

Weight: 16.0 kg





Matic 80
SEMI-AUTOMATIC

Regular/ reinforced tape Width 40- 80 mm Stripe length 100- 750mm 1 length setting Device dimensions: 480 x 250 x 320 mm

Weight: 8.4 kg



ADHESIVE TAPE

EFFECTIVE, ENDURING, AND ECOLOGICAL

The tape is made of very strong Kraft paper coated with vegetable glue. The glue features excellent adhesive and sealing properties, much better than plastic tapes. In the course of application, glue penetrates a layer of paper, creating a very strong and tight bond.

The product can also glue together surfaces that are wet or dusty.

This property is particularly important in cold storage vessels and large distribution centres. An adhesive tape is a product that is 100% recyclable and harmless for the environment.

The most commonly applied tapes are 60/70/80 mm wide and are offered in brown or white. Upon request, tapes in other colours are available. Multi-colour prints are available as well.

To provide a tape with even better resistance parameters, it is reinforced with polyester or glass fibres.



REGULAR ADHESIVE TAPE



REINFORCED TAPE 2 x PARALLEL 1 x WAVE



REINFORCED TAPE 2 x



TAPE REINFORCED
WITH MESH



AUTOMATIC DISPENSEF

AUTOMATIC DISPENSERS

ZUMET

Zumet is designed to seal standard flap cardboard boxes used as collective packaging. Flaps are combined from the top and bottom simultaneously with an adhesive tape.







The machine is available in the version 'with an operator' and in the fully automatic unattended version.



Specification:

Regular or reinforced tape
Tape width 50- 100 mm

Cardboard box sized from 100×120 to 600×650 mm

Minimum box length 100 mm

Maximum box weight 30 kg

Working height 650-800 mm, regulated

Efficiency 12-15 boxes/minute